ULTRA-CONTROLO

Variable-Area Flowmeters

Twin Air Flowmeter, 0-15 l/min

OXYGEN THERAPY & ASPIRATION

Variable-Area Flowmeters

Twin Air Flowmeter, 0-15 l/min

Double variable area flowmeter for doubling the single usage, available with 0-15 l/min flowmeter; it can be connected to the network by means of couplings AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, G 1/4" M RH thread.



Features

- Two 0-15 l/min meters
- Air 400

Standards

- NF S 90-116
- UNI 9507
- EN ISO 15002
- DIN 13260-2
- BS 5682
- EN ISO 15001

Components

- Internal body in chemically nickel-plated aluminium
- External body made of MAKROLON
- AISI 316 stainless steel float
- 1 × inlet with standard probe or G 1/4" M RH thread
- 1 × G 1/4" M RH or M12x1.25 M RH and 9/16" threaded outlet
- Brass adjuster knob with NYLON 6.6 terminal unit
- EPDM or silicone O-Ring
- Internal graduated rotameter column and external MAKROLON 2458 polycarbonate column

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
Air 400	G 1/4" M RH	G 1/4" M	0-15 l/min	4.5
Air 400	UNI 9507	G 1/4" M	0-15 l/min	4.5
Air 400	AFNOR NF S 90-116	G 1/4" M	0-15 l/min	4.5
Air 400	AFNOR NF S 90-116	M12x1.25 M	0-15 l/min	4.5
Air 400	DIN 13260-2	G 1/4" M	0-15 l/min	4.5
Air 400	BS 5682	G 1/4" M	0-15 l/min	4.5