ULTRA-CONTROLO

Variable-Area Flowmeters

Rail High-Flow Flowmeter, 0-30 l/min

OXYGEN THERAPY & ASPIRATION

Variable-Area Flowmeters

Rail High-Flow Flowmeter, 0-30 l/min



High flow rate variable area flowmeter; scale from 0-30 l/min; it can be connected to the medical gas distribution plant by means of suitable couplings in accordance with AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, SS, G 1/4" M RH thread.

Features

- Rail-mount 90° + 1.5 m hose
- 0-30 l/min

Standards

- NF S 90-116
- UNI 9507
- EN ISO 5359
- EN ISO 15002
- DIN 13260-2
- BS 5682
- SS 8752430

Components

- Internal body in chemically nickel-plated aluminium
- External body made of MAKROLON
- AISI 316 stainless steel float
- 1 × inlet with standard probe or G 1/4" M RH thread
- 1 × G 1/4" M RH or M12x1.25 M RH and 9/16" threaded outlet
- Brass adjuster knob with NYLON 6.6 terminal unit
- EPDM or silicone O-Ring
- Internal graduated rotameter column and external MAKROLON 2458 polycarbonate column
- ABS rail clamp
- PVC medical hose Ø6x12

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
O2	AFNOR NF S 90-116 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5
O2	DIN 13260-2 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5
O2	BS 5682 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5
Air 400	AFNOR NF S 90-116 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5
Air 400	DIN 13260-2 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5
Air 400	BS 5682 - 90° - 1.5 m hose	G 1/4" M	0-30 l/min	4.5