ULTRA-CONTROLO

Variable-Area Flowmeters

Twin High-Flow Flowmeter, 0-30 l/min

OXYGEN THERAPY & ASPIRATION

Variable-Area Flowmeters

Twin High-Flow Flowmeter, 0-30 l/min

Double variable area flowmeter, composed of two 0-30 l/min flowmeters; it can be connected to the plant by means of AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, G 1/4" M RH threading.



Features

- Two 0-30 l/min meters

Standards

- NF S 90-116
- UNI 9507
- EN ISO 15002
- DIN 13260-2
- BS 5682
- EN ISO 15001
- SS 8752430

Components

- Internal body in chemically nickel-plated aluminium
- External body made of MAKROLON
- AISI 316 stainless steel float
- 1 × inlet with standard probe or G 1/4" M RH thread
- 1 × G 1/4" M RH or M12x1.25 M RH and 9/16" threaded outlet
- Brass adjuster knob with NYLON 6.6 terminal unit
- EPDM or silicone O-Ring
- Internal graduated rotameter column and external MAKROLON 2458 polycarbonate column

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE 1 + SCALE 2	BAR
O2	G 1/4" M RH	G 1/4" M	0-30 l/min + 0-30 l/min	4.5
O2	AFNOR NF S 90-116	G 1/4" M	0-30 l/min + 0-30 l/min	4.5
O2	DIN 13260-2	G 1/4" M	0-30 l/min + 0-30 l/min	4.5
O2	BS 5682	G 1/4" M	0-30 l/min + 0-30 l/min	4.5
O2	SS 8752430	G 1/4" M	0-30 l/min + 0-30 l/min	4.5
O2	AFNOR NF S 90-116	M12x1.25 M	0-30 l/min + 0-30 l/min	4.5