ULTRA-CONTROLO

Fixed-Point Dispensers

Fixed-Point Oxygen Dispenser, 0-30 l/min

FLOWMETERS & ASPIRATION

Fixed-Point Dispensers

Fixed-Point Oxygen Dispenser, 0-30 l/min

Trigger flowmeter for medical gas delivery. Flow rate is guaranteed by calibrated orifices. Suitable for heavy-duty and emergency-rescue vehicle service. Supplied with UNI, AFNOR, DIN, BS and SS 8752430 connection profiles.



Features

- Trigger flowmeter, 0-30 l/min
- Calibrated orifices
- Multiple inlet standards

Standards

- NF S 90-116
- UNI 9507
- EN ISO 15002
- DIN 13260-2
- BS 5682
- SS 8752430

Components

- Chemically nickel-plated brass body
- AISI 316 stainless steel diaphragm with calibrated holes
- Inlet with specific gas coupling or G 1/4" M RIGHT thread
- Outlet threaded G 1/4" M RIGHT or M12x1.25 M RIGHT
- ABS click adjustment knob
- EPDM and silicone O-ring seal

All variants at 4.5 bar.

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
O2	G 1/4" M	G 1/4" M	0-30 l/min	4.5
O2	UNI 9507	G 1/4" M	0-30 l/min	4.5
O2	AFNOR NF S 90-116	G 1/4" M	0-30 l/min	4.5
O2	DIN 13260-2	G 1/4" M	0-30 l/min	4.5
O2	BS 5682	G 1/4" M	0-30 l/min	4.5
O2	SS 8752430	G 1/4" M	0-30 l/min	4.5
O2	G 1/4" M	M12x1.25 M	0-30 l/min	4.5
O2	AFNOR NF S 90-116	M12x1.25 M	0-30 l/min	4.5
O2	G 1/4" M	9/16" UNF M	0-30 l/min	4.5
O2	UNI 9507	9/16" UNF M	0-30 l/min	4.5
O2	AFNOR NF S 90-116	9/16" UNF M	0-30 l/min	4.5
O2	DIN 13260-2	9/16" UNF M	0-30 l/min	4.5
O2	BS 5682	9/16" UNF M	0-30 l/min	4.5
O2	SS 8752430	9/16" UNF M	0-30 l/min	4.5