ULTRA-CONTROLO

Fixed-Point Dispensers

Dual-Outlet Oxygen Dispenser, 0-30 l/min

FLOWMETERS & ASPIRATION

Fixed-Point Dispensers

Dual-Outlet Oxygen Dispenser, 0-30 l/min

Splitter version of the trigger flowmeter. Flow rate is guaranteed by calibrated orifices. Supplied with UNI, AFNOR, DIN, BS and SS 8752430 connection profiles. Materials include AISI 316 stainless steel and ABS.



Features

- Splitter output
- 0-30 l/min

Standards

- NF S 90-116
- UNI 9507
- EN ISO 15002
- DIN 13260-2
- BS 5682
- SS 8752430

Components

- Chemically nickel-plated brass body
- AISI 316 stainless steel diaphragm with calibrated holes
- Inlet with specific gas coupling or G 1/4" M RIGHT thread
- Outlet threaded G 1/4" M RIGHT or M12x1.25 M RIGHT
- ABS click adjustment knob
- EPDM and silicone O-ring seal

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
O2	UNI 9507	G 1/4" M	0-30 l/min	4.5
O2	AFNOR NF S 90-116	G 1/4" M	0-30 l/min	4.5
O2	DIN 13260-2	G 1/4" M	0-30 l/min	4.5
O2	BS 5682	G 1/4" M	0-30 l/min	4.5
O2	SS 8752430	G 1/4" M	0-30 l/min	4.5
O2	AFNOR NF S 90-116	M12x1.25 M	0-30 l/min	4.5