ULTRA-CONTROLO

Variable-Area Flowmeters

Floating-Sphere Air Flowmeter, 0-15 l/min

FLOWMETERS & ASPIRATION

Variable-Area Flowmeters

Floating-Sphere Air Flowmeter, 0-15 l/min

The flowmeter is used to supply medical gases such as air or oxygen; it can be connected to the gas distribution system using suitable AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682 compliant probes or probes with a G 1/4" M RH thread.



Features

- Floating-sphere indicator
- 0-15 l/min
- Multiple probe standards

Standards

- NF S 90-116
- UNI 9507
- EN ISO 5359
- EN ISO 15002
- DIN 13260-2
- EN ISO 15001
- SS 8752430

Components

- Internal body in chemically nickel-plated aluminium
- External body made of MAKROLON
- AISI 316 stainless steel float
- 1 × inlet with standard probe or G 1/4" M RH thread
- 1 × G 1/4" M RH or M12x1.25 M RH and 9/16" threaded outlet
- Brass adjuster knob with NYLON 6.6 terminal unit
- EPDM or silicone O-Ring
- Internal graduated rotameter column and external MAKROLON 2458 polycarbonate column

GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
Air 400	G 1/4" M	G 1/4" M	0-15 l/min	4.5
Air 400	AFNOR NF S 90-116	G 1/4" M	0-15 l/min	4.5
Air 400	AFNOR NF S 90-116	M12x1.25 M	0-15 l/min	4.5
Air 400	DIN 13260-2	G 1/4" M	0-15 l/min	4.5
Air 400	BS 5682	G 1/4" M	0-15 l/min	4.5
Air 400	SS 8752430	G 1/4" M	0-15 l/min	4.5