ULTRA-CONTROLO

Compact Cylinder Regulators

Compact Regulator, 9 Nm^3/h

EMERGENCY & TRANSPORT

Compact Cylinder Regulators

Compact Regulator, 9 Nm³/h

Pressure regulator for cylinders, suitable for use in mobile system on emergency vehicles, equipped of a transducer for reading the cylinder pressure a alarm signalling; the incoming is specification, the output is 1/4" m a 90°, with connection to hose holder for a Ø 6 mm pipe or with afnor socket.



Features

- Cylinder pressure transducer with alarm signal
- Gas-specific UNI-2 inlet
- Ø 6 mm hose holder or AFNOR socket outlet

Standards

- UNI EN ISO 10524-1
- UNI CEI EN ISO 14971
- UNI CEI EN ISO 13485
- UNI EN ISO 15001

Maintenance kits

- O2 · Maintenance kit, H.P. nylon

Components

- 1 × High Pressure regulator with chemically nickel-plated CW617N brass body
- 1 × gas-specific inlet
- 1 × Ø 6 mm hose connector on the outlet or with Afnor socket
- 1 × overpressure discharge valve, built into the pressure regulator, pre-calibrated and with drain channel, G1/4" M R
- 1 × High Pressure gauge with range according to the gas used, class 2.5
- 1 × Low Pressure gauge with range according to the gas used, class 2.5
- 1 × stainless steel inlet filter with filtration grade > 100 mm
- Stainless steel springs
- EPDM PEROX membrane
- NYLON seal seat
- EPDM PEROX O-Ring

Q MAX.	P1 MAX.	P2	TRANSDUCER 0/315	INLET CONNECTION	OUTLET CONNECTION	WEIGHT
9 Nm³/h	200 bar	4.6 bar	No	UNI-2	Ø 6 mm hose connector	0.90 kg
9 Nm³/h	200 bar	4.6 bar	Yes	UNI-2	Ø 6 mm hose connector	0.90 kg
9 Nm³/h	200 bar	4.6 bar	No	UNI-2	AFNOR terminal unit	0.90 kg
9 Nm³/h	200 bar	4.6 bar	Yes	UNI-2	AFNOR terminal unit	0.90 kg