ULTRA-CONTROLO

Accessories

Pressure Gauge, Electrical Contact

COMPRESSED GAS CONTROL MODULES

Accessories

Pressure Gauge, Electrical Contact

Electromechanical pressure switch with electrical contact compatible for medical use, class 2.5; suitable for signalling the minimum ramp pressure; 1/4" M threaded connection for installation on the interception group of medical gas units.



Features

- Electromechanical switch
- Class 2 medical use

Standards

- UNI EN 837-1
- UNI EN ISO 7396-1
- UNI EN 12094-10
- UNI EN ISO 15001

Components

- Connection thread: 1/4" BSP
- Body Brass
- DOUBLE EPDM gaskets
- NO / NC contacts
- Electrical Features:
- Max Load: 0.5 A at 250 Volt AC, 0.15 A at 110 Volt DC
- Exchange contacts (Common, NO and NC) - SPDT
- Electrical connection according to DIN 43650 standards
- Max voltage 250 VAC - 110 VDC
- Max current A.C. 0.5 A - D.C. 0.15 °
- Max pressure 300 bar
- Operating temperature: -25 °C to + 85 °C
- Insulator / Hardener Epoxy resin
- Max tightening torque 35 Nm
- IP65 protection
- Degreased use oxygen

THREAD	DOWNWARD CALIBRATION	GAS
1/4" G	25 bar down	All
1/4" G	35 bar down	All
1/4" G	100 bar down	All

Tel. +351 21 915 4350

www.ultracontrolo.com