ULTRA-CONTROLO

Terminal Unit Sockets & Base Blocks

Socket - SS 8752430

TERMINAL UNITS

Terminal Unit Sockets & Base Blocks

Socket - SS 8752430

The SS terminal unit conforms to SS 8752430 meets the requirements of functionality, security, innovation and design; the socket has a brass body and a male clutch locking system with steel balls; the coupling flange with the base is adjustable to be able to position the terminal in the desired orientation.



Features

- SS 8752430 compliant
- Adjustable coupling flange
- Single-cartridge maintenance
- NFC traceability

Standards

- UNI EN ISO 9170-1
- UNI EN ISO 15001
- SS 8752430

Components

- Socket and base made of CW614N chemically nickel-plated brass
- Release ring nut
- Stainless steel springs
- EPDM perox O-Ring

Maintenance kits

- O2 - Air 400 - Air 800 - Ar - CO2 - N2O - O2/N2O · Maintenance cartridge SS socket diam. 7 - N°5
- Vac · Maintenance cartridge SS socket diam. 9 - N°6

All variants: 0.11 kg.

GAS	WEIGHT
Air 400	0.11 kg
Air 800	0.11 kg
CO2	0.11 kg
Mix O2/N2O	0.11 kg
N2	0.11 kg
N2O	0.11 kg
O2	0.11 kg
Vac	0.11 kg