ULTRA-CONTROLO

Accessories

Low-Pressure Transmitter, 4-20 mA

SECOND STAGE REDUCER MODULES

Accessories

Low-Pressure Transmitter, 4-20 mA

Pressure transmitter compatible for medical use; in Aisi 316L stainless steel, suitable for signalling minimum and maximum line pressure; 1/4" M threaded connection for installation on the 2nd stage reduction unit for medicines; degreased for oxygen use, complete with cable.



Features

- AISI 316L stainless steel
- 1/4" G connection
- Degreased for O2 service
- 4-20 mA output

Standards

- UNI EN 837-1
- UNI EN ISO 7396-1
- UNI EN 12094-10
- UNI EN ISO 15001

Components

- Connection thread: 1/4" G
- Body in Aisi 416L
- Connector in Polyarylamide 50% GF UL 94 V-0
- Electrical Features:
- Output / Power supply: 4-20 mA - 7. 33 VDC
- Connection with 1.5 m cable
- Max pressure 16 bar
- Operating temperature:
- Process fluids -40. +135 °C
- Environment -30. +85 °C
- Storage -50. +100 °C
- Insulator / Hardener Epoxy resin
- Max tightening torque 35 Nm
- IP 67 protection
- Degreased use oxygen

CONNECTION	PRESSURE	OUTLET/POWER SUPPLY	GAS
1/4" G	0-16 bar	4-20 mA / 7-33 VDC	All