ULTRA-CONTROLO

NIST ISO 18082

Threaded Socket - NIST ISO 18082

TERMINAL UNITS

NIST ISO 18082

Threaded Socket - NIST ISO 18082

NIST socket per EN ISO 18082 connected to the medical gas distribution system by a G 1/4" M DX or G 3/8" M DX threaded connection. Also available in a "free flow" version without integrated check valve.



Features

- G 1/4" or G 3/8" M DX thread
- With or without check valve

Standards

- UNI EN ISO 9170-1
- UNI EN ISO 15001
- UNI EN ISO 18082

Components

- One chemically nickel-plated brass terminal unit body
- One G1/4" M R or G3/8" M R threaded connector
- One stainless steel spring
- One sintered bronze filters (filtration grade 100 µm)
- One EPDM PEROX O-Ring

All variants: 0.13 kg.

GAS	TYPE	WEIGHT
Air 800	G1/4" M DX	0.13 kg
O2	G1/4" M DX	0.13 kg
Air 400	G1/4" M DX	0.13 kg
Vac	G1/4" M DX	0.13 kg
N2O	G1/4" M DX	0.13 kg
CO2	G1/4" M DX	0.13 kg
O2	Free flow	0.13 kg
Air 400	Free flow	0.13 kg
Air 800	Free flow	0.13 kg
Vac	Free flow	0.13 kg
N2O	Free flow	0.13 kg
CO2	Free flow	0.13 kg
O2	G3/8" M DX	0.13 kg
Air 400	G3/8" M DX	0.13 kg
Air 800	G3/8" M DX	0.13 kg
Vac	G3/8" M DX	0.13 kg
N2O	G3/8" M DX	0.13 kg
CO2	G3/8" M DX	0.13 kg