ULTRA-CONTROLO

DIN 13260-2

Recessed Socket - DIN 13260-2

TERMINAL UNITS

DIN 13260-2

Recessed Socket - DIN 13260-2

The socket is DIN 13260-2 standard compliant; the socket is the final part of the compressed gas distribution system and the user can plug a probe into the socket to use the gas; the socket is gas-specific and various profiles are available depending on the gas being used so it is impossible to swap sockets and probes.



Features

- DIN 13260-2 compliant
- 6 mm hose or G 1/4" M DX connection

Standards

- UNI EN ISO 9170-1
- DIN 13260-2
- UNI EN ISO 15001

Components

- Socket and base made of CW617N chemically nickel-plated brass
- CW617N chemically nickel-plated brass release ring nut and base connecting flange
- Stainless steel springs
- EPDM PEROX O-Ring

All variants: 0.17 kg.

GAS	CONNECTION	WEIGHT
O2	Hose Ø 6 mm	0.17 kg
Air 400	Hose Ø 6 mm	0.17 kg
N2O	Hose Ø 6 mm	0.17 kg
Vac	Hose Ø 6 mm	0.17 kg
CO2	Hose Ø 6 mm	0.17 kg
O2	G 1/4" M DX	0.17 kg
Air 400	G 1/4" M DX	0.17 kg
N2O	G 1/4" M DX	0.17 kg
Vac	G 1/4" M DX	0.17 kg
CO2	G 1/4" M DX	0.17 kg